


Tile Movement Joints

CATALOGUE

NEXUS
Tile Movement Joints



UNITECH
for Building and Construction Materials
www.unitech-ikk.com

IKK Group of Companies
www.ikkgroup.com



Features

NEXUS manufacture Tile Movement Joints that are used on floors to protect tile edges and to accommodate movements and local stresses.

The most common problems for Tile fixings are Tile pop-outs and sealant failure. Using tile joints is a suitable and economic solution to avoid problems related to the fixing tiles.

Sealants are used for the economic viability and easiness in application and due to their poor load bearing capacity, sealants often fail resulting in cracks and fissures along the line of application



Tile Movement Joints are best suited replacement for such situations and suitable for use with Ceramic, Terrazzo, Marble, Stone and other similar materials.

NEXUS Movement Joints are manufactured using high quality Brass, Stainless Steel, Aluminum with plates bonded to a neoprene or EPDM rubber inserts.

NEXUS Movement Joints are manufactured in accordance to the following international standards:


Country	Standard	Recommended By Sizes	
		Internal	External
USA	ANSI A108.1 installation of ceramic tiles.	6.0m-8.0m	3.6m-4.8m
UK	BS 5385-Part3:1989 Code of practice for the design and installation of ceramic floor tiles and mosaics	8.0m-10.0m	4.5m-6.0m
FRANCE	NF P 61.2021 / DTU 52.1 Sealed floor coverings NF P 14-201-1 / DTU 26.2 Treads and tiles to bases hydraulic binders	6.0m-8.0m	3.5m-4.0m
AUSTRALIA	AS 3958.1 - 1991 Guide to the installation of ceramic tiles	8.0m-10.0m	4.5m-6.0m

NEXUS

Tile Movement Joints

Amongst the many factors causing ceramic tiles to move, are significant changes in atmospheric temperature, weight loading, traffic density, rigid attachments such as fixed plant, pillars etc. and thermal and moisture movements in the structural base, background and tiling.


NEXUS Movement Joints create a tile field which moves independently from those around it, and should be included at set distances in floor and wall tiles, in accordance with recommendations from the British Standards Institution (BSI).



A typical installation should include Movement Joints within the tiled area itself and on internal corners of walls, along with the floor to wall connection. They should also be used at the perimeter of application of over two meters or where there is excessive thermal and vibration movement. Installers and specifiers should always refer to the BSI recommendations for specific applications. There are different widths of performed movement joints, and the correct width and material must be specified to take thermal movement into account, along with traffic density.



The BSI states that ultimately the specifier is responsible for choosing the right joints and deciding where they will be positioned. In a nutshell, aluminum is ideal for commercial use, whereas brass and stainless steel are used for heavy commercial and industrial projects such as warehousing, production facilities Malls and airports and where the tiled surface is cleaned by scrubbing machine, or where there are rolling loads such as pallet trucks and metal-rimmed trolleys. Stainless Steel is also ideal where chemicals are used, such as laboratories and food processing plants.



NMJ-2L

NEXUS
CODE
NMJ-2L

Features


Tile Movement Joint NMJ-2L is manufactured using 1.5mm side plates of Brass, Stainless Steel or Aluminum bonded firmly to a rubber insert of 7mm thickness.

The side plates range from 10mm onwards to maximum of 100mm in height and another sizes can be specially ordered.

Rubber inserts are available in 10 standard colours. All profiles are fabricated for a cut length of 2.44mm or any required length less than 2.44mm.



APPLICATIONS MOVEMENT JOINTS



*Note: Available Height 10/15/20/25mm.

Any other sizes / shapes are available upon request.

Features


Tile Movement Joint NMJ-1L is manufactured using one flat side plate on side and L-plate on the other side bonded to the rubber insert.

These profiles are particularly useful for perimeter fixing or an existing finished area.

Rubber insert are available in 10 standard colours. All profiles are fabricated for a cut length of 2.44mm or any other required length less than 2.44mm.



APPLICATIONS MOVEMENT JOINTS



*Note: Available Height 10/15/20/25 mm.
Any other sizes / shapes are available upon request.

NEXUS

Tile Movement Joints

NMJ-S

NEXUS
CODE
NMJ-S

Features


Tile Movement Joint NMJ-S is manufactured using 1.5mm side plate of Brass, Stainless Steel or Aluminum bonded firmly to a rubber insert of 7mm.

The side plates range from 15mm onwards to maximum of 100mm in height and can be specially ordered for a greater thickness for heavy duty applications.

Rubber inserts are available in 10 standard colours. All profiles are fabricated for a cut length of 2.44mm or any other required length less than 2.44mm.



APPLICATIONS MOVEMENT JOINTS



*Note: Available Height 15/20/25/30mm.

Any other sizes / shapes are available upon request.



BETA CONTECH
National Specialized Construction Technologies



unitech.uae @ikkgroup.com
ikk group.com

MATERIAL SPECIFICATIONS

Material	Grade / Alloy	Related Standards
Stainless Steel	(304) / (1.4301) (316) / (1.4404)	BSEN 10088-2:2014 BSEN 10088-2:2014
Aluminum	EN AW-6060 EN AW-6063	BSEN 12020-1:2008 BSEN 12020-2:2008
Brass	Copper Alloys Bronze Alloys CuZn43Pb2Al(CW624N)	BSEN 1652:1998 GOST 15527-2004

NEOPRENE

Temperature Range: - 35 to 100°C

I .PHYSICAL PROPERTIES

Sl.Nr.	DESCRIPTION	TEST METHOD	UNIT	SPECIFICATION
1	Hardness	ISO 7619	Shore A	60± 5
2	Specific Gravity	ISO 2781	-	1.33±0.05
3	Tensile Strength, Min.	ISO 37	MPa	15.5
4	Elongation At Break, Min.	ISO 37	%	350
5	Compression Set, Max. (22hrs@100°C)	ISO 815	%	35
6	Accelerated ageing resistance. (70 hrs@ 100°C)	ISO 188	-	-
6.1	Change in Hardness	ISO 7619	Shore A	+15
6.2	Change in Tensile Strength, Max.	ISO 37	%	-15
6.3	Change in Elongation at Break, Max.	ISO 37	%	-40

II .GENERAL PROPERTIES :

7	Resistance to UV	Excellent
8	Resistance to Water	Good
9	Resistance to Acids	Good
10	Resistance to Alkalis	Good
11	Resistance to H2S	Good
12	Resistance to Natural Gas	Fair
13	Resistance to Aliphatic Hydrocarbons	Good
14	Resistance to Ketones	Fair
15	Resistance to Alcohols	Fair
16	Resistance to Lubricating Oils	Good
17	Resistance to Hydraulic Oils	Good
18	Resistance to Fuels	Good
19	Resistance to Weathering	Excellent
20	Resistance to Oxidative	Good

EPDM


Temperature Range: - 35 to 100°C

I .PHYSICAL PROPERTIES :

Sl.Nr.	DESCRIPTION	TEST METHOD	UNIT	SPECIFICATION
1	Hardness	ISO 7619	Shore A	70±5
2	Specific Gravity	ISO 2781	-	1.18±0.05
3	Tensile Strength, Min.	ISO 37	kg/cm2	100
4	Elongation At Break, Min.	ISO 37	%	300
5	Compression Set, Max. (22hrs@100°C)	ISO 815	%	35
6	Accelerated ageing resistance. (24hrs@100°C)	ISO 188	-	-
6.1	Change in Hardness	ISO 7619	Shore A	± 5
6.2	Change in Tensile Strength, Max.	ISO 37	%	-15
6.3	Change in Elongation at Break, Max.	ISO 37	%	-25


II .GENERAL PROPERTIES :

7	Resistance to UV	Excellent
8	Resistance to Water	Excellent
9	Resistance to Acids	Fair
10	Resistance to Alkalis	Fair
11	Resistance to Aliphatic Hydrocarbons	Fair
12	Resistance to Hydraulic Oils	Good
13	Resistance to Fuels	Fair
14	Resistance to Weathering	Excellent
15	Resistance to Oxidative ageing	Good







STANDARD COLORS




Milky White



Alabaster




Light Beige



Linen




Sandstone



Light Smoke



Earth



Light Grey



Pewter



Black

LOCATIONS

KINGDOM OF SAUDI ARABIA unitech.ksa@ikkgroup.com

Jeddah (Head Quarters)
Tel : +966 12 627 8222
Fax: +966 12 627 8722

UNITED ARAB EMIRATES unitech.uae@ikkgroup.com

Dubai - Dubai Industrial City (Head Quarters)
Tel : +971 4 818 1900

Abu Dhabi - Musaffah
Tel: +971 2 552 3393
Fax: +971 2 552 5499

Dubai - Al Rashidiyah
Tel : +971 4 2591 773
Fax : +971 4 2591 774

OMAN unitech.oman@ikkgroup.com

Muscat
Tel : +968 24 591 006
Fax : +968 24 597 006

JORDAN unitech.jordan@ikkgroup.com

Amman
Tel : +962 6 556 3030
Fax: +962 6 554 7911

EGYPT unitech.egypt@ikkgroup.com

Cairo 6th of October City
Tel : +20 2 3820 6477
Fax: +20 2 3820 6036

GERMANY unitech.germany@ikkgroup.com

Stuttgart
Tel : +49 711 6868 7222
Fax: +49 711 6868 7223

QATAR unitech.qatar@ikkgroup.com

Doha
Tel : +974 4451 3301/2/3
Fax : +974 4451 3305

LEBANON unitech.lebanon@ikkgroup.com

Beirut
Tel : +961 1 858 277
Fax: +961 1 858 276

FACTORIES

SFSP - KSA
sfsp.jeddah@ikkgroup.com


Specialized Factory for Steel Products
3rd Industrial City / Jeddah
Tel: +966 12 637 4482
Fax: +966 12 636 1963



SFSP / UAE
sfsp.uae@ikkgroup.com

SIGMA Factory for Steel Products
DIC (Dubai Industrial City)
Tel : +971 4 818 1919





Produced in Lebanon by

multi

www.multid-ikk.com

PP-CT-BCM01-M19